

Qualified Federal Tax Credit Windows: SHGC ≤ .30 and U-Factor ≤ .30

Style	Series	Glass	Gas	U-Factor	Solar Heat Gain Coefficient	Condensation Resistance	Visible Transmittance	DP Rating
Single Hung	200	366	Argon	0.30	0.22	57	0.52	40
Single Hung	200	270	Argon	0.30	0.30	57	0.56	40
Picture Window	200	366	Argon	0.29	0.23	59	0.54	55
Horizontal Slider	200	270	Argon	0.30	0.30	57	0.56	55
Picture Window	500	366	Argon	0.29	0.22	58	0.49	50
Picture Window	500	366	Argon	0.29	0.22	58	0.49	50
Picture Window	500	366	Argon	0.29	0.22	58	0.49	50
Picture Window	500	366	Argon	0.27	0.22	61	0.51	50
Casement	500	366	Argon	0.30	0.28	57	0.46	-
Casement	500	366	Argon	0.30	0.28	57	0.46	-
Casement	500	366	Argon	0.30	0.27	57	0.46	60
Casement	500	366	Air	0.30	0.19	57	0.43	-
Casement	500	366	Argon	0.27	0.18	60	0.43	-
Casement	500	270	Argon	0.30	0.28	57	0.46	-
Casement	500	270	Argon	0.30	0.28	57	0.46	-
Casement	500	270	Argon	0.30	0.27	57	0.46	60
Casement	500	270	Argon	0.28	0.28	60	0.48	-
Picture Window	700	366	Argon	0.27	0.22	58	0.52	55
Casement	700	366	Argon	0.28	0.20	61	0.46	-
Casement	700	270	Argon	0.28	0.30	61	0.52	-
Awning	700	366	Argon	0.28	0.20	60	0.46	-
Awning	700	270	Argon	0.28	0.30	60	0.52	-
Slider	800	366	Argon	0.30	0.21	57	0.50	-
Double Hung	800	366	Argon	0.30	0.21	56	0.50	30